

Thermic 6.5

CRANKSHAFT



Standard equipment:

- 3.700.0036 Industrial Gun



- 6.002.0322 Industrial Steel Spray Lance



- 4.618.0166 10M Steel Braid HP Hose



- 0.999.1003 QR Nozzles



- 3.749.0472 Turbo Head



Optional:

- 6.602.0051 Industrial Foaming Lance

(* Requires
0.999.0104
Coupling)



- 0.100.1004 15" Whirl-A-Way



* More Options Available

Equipped with:

- 3 Ceramic Coated Pistons
- Brass Linear Pump Head with Built-In Bypass Valve
- LAVOR Industrial Crankshaft Pump (CL3) Rated at 1500 Hours
- Suction and Delivery Stainless Steel Valves
- Loncin 6.5HP Unleaded Petrol Engine with **2 Year Warranty**
- Integrated Detergent Suction with External Suction Probe
- Pressure Regulator
- Steel Frame

THERMIC 6.5	
Code	8.601.0185
Max Operating Pressure	3000 PSI
Maximum Water Volume	10.5 Litres/Minute, 630 Litres/Hour
Motor Specifications	6.5 HP Unleaded Petrol - 4 Stroke
Pump Type/RPM	CL3 / 3600
Max. Water Inlet Temperature	40 °C
Dimension/Weight	60x50x60cm/37 Kg