




HYPER C



Equipped with:


- Four Pole Electric Motor with Thermal Protection and Water Cooling (Cooling on 415v models only)
- Three Ceramic Pistons
- Brass Crankshaft Pump Head with Built-In By-Pass Valve
- Integrated Elastic Motor/Pump Coupling for Shock Absorption
- Low Voltage (415v models only) and Delayed Total Stop
- Integrated Detergent Suction with External Suction Probe
- Suction and Delivery Stainless Steel Valves
- Pressure Regulator
- Glycerine Pressure Gauge
- Steel Frame and Stainless Steel Cover

Standard equipment:

- 00080-01695 - AL55 Industrial Gun



- 00080-01733 Industrial Spray Lance



- 00080-02347 10M Double Steel Braided Hose



- 00080-03149 Nozzle
- 00080-03158 Nozzle (HYPERC2021 Only)



Optional:

- 6.602.0051 Industrial Foaming Lance (* Requires 0.999.1015 Coupling)



- 0.999.0126 Turbo Lance (1211 and 2015 model)

- 0.999.0128 Turbo Lance (2021 model)



- 0.999.0100 20M Dbl Steel Braided Hose
- 0.999.0130 30M Dbl Steel Braided Hose

(* Requires 00009-02101 Coupling)



* More Options Available

	HYPER C 1211 (240v)	HYPER C 2015 (415v)	HYPER C 2021 (415v)
Code	36082-00077	36082-00143	36082-00144
Standard Operating Pressure	1800 PSI	3000 PSI	3000 PSI
Maximum Water Volume	11.6 Litres/Minute, 700 Litres/Hour	15 Litres/Minute, 900 Litres/Hour	21 Litres/Minute, 1260 Litres/Hour
Motor Specifications	240V(15 Amp), 1Ph, 3.0KW(4.0HP)	415V(20 Amp), 3Ph, 7.0KW(9.3HP)	415V(20 Amp), 3Ph, 9.4KW(12.5HP)
Pump Type/RPM	CL5/1450	CL5/1450	CL5/1450
Max. Water Outlet Temperature	40 °C	40 °C	40 °C
Dimension/Weight	55x60x60cm/56 Kg	55x60x60cm/56 Kg	55x60x60cm/58 Kg