




LKX1310LP




Standard equipment:

- 00080-01695 - M22 Industrial Gun



- 00080-01715 Industrial Spray Lance



- 00080-02347 10M Double Steel Braided Hose



- 00080-03149 Nozzle



Equipped with:

- Four Pole Electric Motor with Thermal Protection
- Three Ceramic Coated Pistons
- Brass Crankshaft Pump Head with Built-In By-Pass Valve
- Low Voltage and Delayed Total Stop
- Suction and Delivery Stainless Steel Valves
- Vertical Burner with High Thermal Efficiency Steel Coil
- Adjustable Temperature Thermostat
- Detergent Tank for Indirect Suction
- Low Fuel Safety Cut Out



Optional:

- 6.602.0051 Industrial Foaming Lance
(* Requires 0.999.1015 Coupling)



- 0.999.0126 Turbo Lance



- 0.999.0100 20M Dbl Steel Braided Hose
- 0.999.0130 30M Dbl Steel Braided Hose

(* Requires 00009-02101 Coupling)



* More Options Available

| LKX1310LP | |
|-------------------------------|-----------------------------------|
| Code | 36072-00183 |
| Standard Operating Pressure | 1800 PSI |
| Maximum Water Volume | 11 Litres/Minute, 660 Litres/Hour |
| Motor Specifications | 240V (15 Amp), 1Ph, 3.0KW (4.0HP) |
| Pump Type/RPM | CL4/1450 |
| Max. Water Outlet Temperature | 140 °C |
| Dimension/Weight | 71x110x110cm/100 Kg |