



HYPER L



CRANKSHAFT



Standard equipment:

- 00080-01694 - AL55 Pressure Adjustable Industrial Gun



- 00080-01727 Industrial Spray Lance



- 00080-02347 10M Double Steel Braided Hose



- 00080-03149 Nozzle



Optional:

- 6.602.0051 Industrial Foaming Lance
(* Requires 0.999.1015 Coupling)



- 0.999.0126 Turbo Lance



- 0.999.0100 20M Dbl Steel Braided Hose
- 0.999.0130 30M Dbl Steel Braided Hose

(* Requires 00009-02101 Coupling)



* More Options Available



Equipped with:

- Four Pole Electric Motor with Thermal Protection and Water Cooling (Cooling on 415v model only)
- Three Coated Pistons
- Crankshaft Pump and Brass Pump Head with Built Valve
- Integrated Elastic Joint
- Low Voltage and Delayed Total Stop
- Equipped with Pressure on Gun
- Vertical Burner with High Thermal Efficiency
- Adjustable Temperature Thermostat
- Detergent Tank for Built In High Pressure Application
- **Stainless Steel Heating Coil with 3 Year Warranty**

	HYPER L 1211 (240v)	HYPER L 2015 (415v)
Code	36072-00197	36072-00137
Standard Operating Pressure	1800 PSI	3000 PSI
Maximum Water Volume	11 Litres/Minute, 660 Litres/Hour	15 Litres/Minute, 900 Litres/Hour
Motor Specifications	240V (15 Amp), 1Ph, 3.0KW (4.0HP)	415V (20 Amp), 3Ph, 7.3KW (9.7HP)
Pump Type/RPM	CL4/1450	CL5/1450
Max. Water Outlet Temperature	140 °C	140 °C
Dimension/Weight	71x113x110cm/109 Kg	71x113x110cm/129 Kg